

02-04 SERIES COMPARISON



TE6502MIS-B1AG | TE7502MIS-B1AG | TE8602MIS-B1AG*



TE5504MIS-B3AG* | TE6504MIS-B3AG | TE7504MIS-B3AG |
TE8604MIS-B3AG | TE9804MIS-B1AG**

ProLite

Display characteristics		
Size category		65", 75" & 86"
Panel type		VA, IPS*
Anti-Glare Coating		✓
Zero Air-Gap		×
Touch technology		Infrared
Touch points		20
Native resolution		3840 x 2160 (4K UHD)
Panel brightness (cd/m ²)		400
Light transmittance		88%
Static contrast		5000:1, 1200:1*
Max. Operating time		16/7
Interfaces & connectors		
Video IN		VGA, 2x HDMI (2.0)
Audio IN / OUT		MiniJack (IN & OUT)
Speakers		2x 10W Speakers (front-faced)
Control		USB (touch) IN, RS232c, RJ45 (Auto switch for PC & Android, 1000MB)
USB		4x USB (2x 2.0 front, 2x 2.0 right side)
Features		
Android / iiWare		Android 9.0 OS/ iiWare 8.0
ScreenSharePro & Eshare		✓
Ambient light sensor		✓
OTA firmware update		✓
Internal memory		16GB
Metal housing		✓
Included / optional		
Wifi Collaboration module		OWM002
Metal housing		✓
Mounting brackets for NUC/webcam		✓
Touch pens (dual function tips)		2x
Optional (OPS) Slot PC		OPC5801BC, OPC51103BC
		55", 65", 75", 86" & 98"
		IPS
		✓
		✓
		PureTouch-IR
		40*, 20
		3840 x 2160 (4K UHD)
		390*, 400
		88%
		1200:1
		24/7
		VGA, 3x HDMI (2.0), USB-C (3.1)
		MiniJack (IN & OUT) / S/PDIF
		2x 16W Speakers
		2x USB (touch) IN, RS232c, 2x RJ45 (Auto switch for PC & Android, 1000MB)
		6x USB (2x 3.0 front, 2x 3.0, 1x 2.0 right side, 1x 3.1 USB-C)
		Android 9.0 OS/ Android 11* OS/ iiWare 9.0
		✓
		✓
		✓
		32GB
		✓
		OWMW002, OWM001**
		✓
		✓ (excl. TE9804)
		4x
		OPC5801BC, OPC51103BC

All trademarks and registered trademarks acknowledged. Changes and mistakes in graphics and specs reserved. Specifications subject to change without notice. Copyright by iiyama International. Stand 08/2022.