



Application Note

ProLite TF3222MC-B2

ProLite TF3238MSC-B2AG

ProLite TF4338MSC-B2AG

ProLite TF6538UHSC-B1/B2

TOUCH THROUGH-GLASS FIRMWARE INSTRUCTIONS

- Connect the screen to a PC with Windows 10
- Unzip the file **Hover SW_TF3238&4338_B2AG_6538_3222-20190604.zip** onto the PC
- Double click **BinfileSelector.exe**

Name	Date modified	Type	Size
FwBinFiles	26/08/2019 12:14	File folder	
iconengines	26/08/2019 12:14	File folder	
imageformats	26/08/2019 12:14	File folder	
nUpdateFW	26/08/2019 12:14	File folder	
platforms	26/08/2019 12:14	File folder	
res	26/08/2019 12:14	File folder	
sqldrivers	26/08/2019 12:14	File folder	
translations	26/08/2019 12:14	File folder	
BinfileSelector.exe	26/08/2019 12:14	Application	51 KB
D3Dcompiler_43.dll	26/05/2010 19:41	Application exten...	2,057 KB
DynamicSiSLog.dll	21/11/2017 14:09	Application exten...	22 KB
libEGL.dll	29/06/2015 19:22	Application exten...	11 KB
libGLSV2.dll	29/06/2015 19:21	Application exten...	1,674 KB
Qt5Core.dll	08/06/2017 12:34	Application exten...	4,540 KB
Qt5Gui.dll	29/06/2015 19:24	Application exten...	4,760 KB
Qt5Sql.dll	29/06/2015 19:22	Application exten...	148 KB
Qt5Svg.dll	29/06/2015 19:32	Application exten...	245 KB
Qt5Widgets.dll	29/06/2015 19:27	Application exten...	4,384 KB

- In the list, select the adequate screen model e.g. **TF4338**
- Select the Mode you wish to use:
 - **Mode 1:** for Cover Glass with **2mm** thickness
 - **Mode 2:** for Cover Glass with **6mm** thickness
- Click **UpdateFW**
- If you wish to go back to Default mode, select OFF and click **UpdateFW**

