

UNIFIED COMMUNICATIONS**INFORMATION**

Professional 4K Webcam with 8 mic array, Auto Framing and Speaker Tracking



The UC-CAM10PRO-MA1 is a professional 4K webcam with auto-framing and speaker tracking with 120° field of view (FoV). Auto framing adjusts to your position, placing the user in view at all times. Equipped with an impressive 5x Digital Zoom and integrated 8 microphone array, the strong audio detection with a range of up to 8 meters and clear zoom performance guarantees all users will be seen and heard. Thanks to a 15° tilt adjustment feature, the camera can be customized to fit your needs. If you are particularly cautious about privacy, a manual privacy shutter ensures your camera can only see you when you want it to. Easy to set up, this lightweight camera works in any and every environment large or small whilst supporting all leading conferencing software like Zoom, Skype, Microsoft Teams and more.



120° field of view

The field of view means the observable area one can see through the camera lens. It translates directly to how much of your meeting space will be visible to the participants joining remotely. A 120-degree FoV is the right solution for most standard meeting spaces.



2D & 3D Digital Noise Reduction

Delivering high image quality, these two image denoising technologies combined ensure crisp and clear visuals for video and photos.



Auto-framing

With intelligent face detection and voice localization, the camera tracks whoever is speaking and smoothly switches between presenters automatically adjusting to best fit participant location and quantity. It not only recognizes and zooms in on meeting participants, but also tracks speakers as they move about the room.



Clear, Crisp and Natural Audio

Featuring an advanced noise reduction algorithm, the integrated 8-element mic array detects audio from up to 8 metres away, delivering high quality audio free from any annoying background noise or distortion.

01 CAMERA

Pixels	8.46M
Разрешение	4K UHD
Supported resolutions	2160p/30fps, 1440p/30fps, 1080p/30fps
Diagonal field of view (dFoV)	120°
Focus mode	fixed
Focus distance	8m
Aperture	2.5
Zoom	5x digital zoom
White balance	yes
Exposure	yes
Backlight compensation	да
AutoFraming	да
Number of camera position presets	1

02 AUDIO

Number of microphone arrays	8
Voice pickup distance	8m
Voice pickup angle	180°
Automatic tracking	да
Noise reduction	да
Automatic gain control	да

03 CONNECTIVITY

Camera	USB Type-C
Host	USB v.3.0

04 MICROPHONE

Number of microphone arrays	x8
Voice pickup range	8m (radius)

05 CONNECTIVITY & BUTTON OPERATIONS

USB Type C	x1
------------	----

06 МЕХАНИЧЕСКИЕ ХАРАКТЕРИСТИКИ

Угол наклона экрана ≤15°

Вращение 360°

Privacy shutter yes

07 6.АКСЕССУАРЫ

Пульт ДУ да (батарейки в комплекте)

Power adapter да

08 СТАНДАРТЫ

Сертификаты CE, FCC-B, RoHS support, ErP, WEEE, REACH

09 РАЗМЕР / ВЕС

Размер продукта Ш x В x Г 300. x 85 x 100мм

Размер коробки Ш x В x Г 300 x 84 x 100мм

Вес (без упаковки) 0.346кг

Вес (с упаковкой) 1кг

EAN код 4948570033157

10 СОПУТСТВУЮЩАЯ ИНФОРМАЦИЯ

Сопутствующие товары [UC CAM120ULB-1](#), [UC CAM180UM-1](#), [UC CAM80UM-1](#), [UC CAM75FS-1](#), [UC SPK01M](#)



Все товарные знаки и торговые марки являются собственностью их владельцев и они защищены. Ошибки и изменения допускаются. Спецификации могут быть изменены без уведомления. Все LCD мониторы соответствуют стандарту ISO-9241-307:2008 по политике битых пикселей. © IIYAMA CORPORATION. ALL RIGHTS RESERVED