



## Panel sa IPS tehnologijom od 27" sa postoljem podesivim po visini i brzinom osvežavanja od 100 Hz

Moderan dizajn od ivice do ivice čini ProLite XUB2792HSU savršenim za povejivanje sa više monitora. Tehnologija IPS panela nudi preciznu i doslednu reprodukciju boja sa širokim uglovima gledanja. Brzina osvežavanja od 100 Hz zajedno sa funkcijom FreeSync obezbeđuje trenutno, opipljivo poboljšanje glatkoće slike. Visoke vrednosti kontrasta i osvetljenosti znače da će monitor pružiti odlične performanse za digitalnu obradu fotografija i veb dizajn. Opremljen zvučnicima, 2 porta USB 3.2, utičnicom za slušalice, HDMI i DisplayPort priključcima, funkcijom redukcije plavog svetla za smanjenje zamora očiju i ergonomskim postoljem podesivim po visini od 150 mm za optimalnu udobnost korisnika, čine ovaj monitor od 27 inča odličnim izborom za više-konfiguracija monitora i kancelarijske aplikacije.

Takođe dostupan u crnoj : [ProLite XUB2792HSU-B6](#)



### IPS Tehnologija

IPS displeji su najpoznatiji po širokim uglovima gledanja i prirodnim, izuzetno tačnim nijansama boja. Posebno su pogodni za primenu u situacijama gde je potrebno prikazati veliki broj nijansi boja.



### Slim Line

Slim Line monitori imaju tanak okvir i zato su posebno pogodni za postavljanje video zida ili upotrebu u konfiguracijama sa više monitora.

## 01 KARAKTERISTIKE EKRANA

Dizajn	Bez rama sa tri strane
Dijagonala	27", 68.6cm
Panel	IPS tehnologija panela, LED; mat završna obrada
Osnovna rezolucija	1920 x 1080 @100Hz (2.1 megapixel Full HD)
Osnovna rezolucija	100Hz
Format ekrana	16:9
Osvetljenje	250 cd/m <sup>2</sup>
Statički kontrast	1300:1
Napredni kontrast	80M:1
Vreme odziva (MPRT)	0.4ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Podržane boje	16.7mln (sRGB: 99%, NTSC 72%)
Horizontalna sinhronizacija	31 - 115KHz
Vidljiva površina Š x V	597.9 x 336.3mm, 23.5 x 13.2"
Razmak piksela	0.311mm
Boja	mat, bela

## 02 KONEKTORI / KONTROLE

Ulaz signala	HDMI x1 DisplayPort x1
USB HUB	x4 (v. 3.2 Gen 1 (5Gbps, DC5V, 900mA))
HDCP	da

## 03 KARAKTERISTIKE

Smanjeno emitovanje plave svetlosti	da
Bez treperenja	da
Adaptive Sync podrška	da
Dodatno	i-Style boje
OSD jezici	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Kontrolni tasteri	Izbor Signala/ Izlaz, + / Jačina zvuka, - / Eko +, Meni , Uključivanje
Korisničke kontrole	podešavanje slike (kontrast, osvetljenost, i-Style boja, ACR, Eco, OD, X-Res tehnologija), podešavanja slike (reduktor plave svetlosti, oštra i mekana, podešavanje video režima), podešavanja boja (gama, 6 osa, temp. ), audio podešavanja (jačina zvuka, isključivanje zvuka), podešavanja na ekranu (OSD H. pozicija, OSD V. pozicija, OSD vreme, rotacija menija na ekranu, jezik), ekstra1 (MBR, AdaptiveSinc, USB BC), ekstra2 (resetovanje, DDC/CI, izbor signala, HDMI opseg, logo otvaranja, LED, informacije)
Zvučnici	2 x 2W
Pogodnost	Kensington-lock™ priprema, DDC/CI, DDC2B, Mac OSX

## 04 MEHANIČKI

Podešavanje položaja prikaza	visina, okretanje, nagib, pivot (rotacija u obe strane)
Podešavanje visine	150mm
Rotacija (PIVOT funkcija)	90°
Okretno postolje	90°; 45° levo; 45° desno
Ugao nagiba	22° gore; 5° dole

VESA montiranje	100 x 100mm
Sistem upravljanja kablovima	da

## 05 UKLJUČENI DODACI

Kablovi	Strujni kabl, USB, HDMI, DP
Ostalo	kratko uputstvo, bezbednosni vodič

## 06 UPRAVLJANJE NAPAJANJEM


Napajanje	interna
Potrošnja energije	% 1W tipično, 0.5W stand by, 0.3W isključen

## 07 ODRŽIVOST

Propisi	TCO Sertifikat, CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS podrška, ErP, WEEE, REACH, UKCA
Klasa energetske efikasnosti (Regulation (EU) 2017/1369)	E
REACH SVHC	iznad 0.1%: Olova

## 08 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	612.5 x 394 (544) x 209.5mm
Dimenzije kutije Š x V x D	690 x 455 x 168mm
Težina (bez kutije)	5.7kg
EAN kod	4948570123360



*All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.*

© IYAMA CORPORATION. ALL RIGHTS RESERVED