



## An Intel® i5 OPS slot PC with Windows® 10 IoT Enterprise and TPM 2.0 (Trusted Platform Module)

This mini OPS PC with Intel® Core™ i5 inside turns your iiyama interactive large format display into a stand-alone solution. It comes equipped with a powerful Intel® processor with integrated Ultra HD graphics and a fast SSD drive. No hassle with cables and having to mount a PC at the back of the monitor or on a floor lift. Simply slide in the iiyama OPS slot PC and get started right away.

The module is standard Intel OPS compatible, including the following iiyama displays: 55": <u>TE5504MIS-B3AG</u>, 65": <u>TE6502MIS-B1AG</u> / <u>TE6504MIS-B3AG</u>, 75": <u>TE7502MIS-B1AG</u> / <u>TE7504MIS-B3AG</u>, 86": <u>TE8602MIS-B1AG</u> / <u>TE8604MIS-B3AG</u> and the 98": <u>TE9804MIS-B1AG</u>

## 01 DEVICE

| Туре                | OPS slot PC   |
|---------------------|---|
| CPU                 | Intel® Core™ i5-8265U, TPM 2.0 (Trusted Platform Module)  |
| RAM                 | 8GB DDR4  |
| SSD                 | 256GB M.2   |
| Graphics            | Intel® UHD Graphics 620                                   |
| Sound card          | Integrated High Definition Audio Stereo                   |
| Network             | 10/100/1000M Adapter                                      |
| WiFi                | 802.11ac (2.4GHz/5GHz)                                    |
| Bluetooth           | 5.0   |
| Operating system    | Win 10 IoT Enterprise 64-bit                              |
| LAN (RJ45)          | x1  |
| USB                 | 3.0 x2, 2.0 x2, 3.1 Type C x1 (DP Alt Mode not supported) |
| HDMI Out            | x1  |
| Headphone connector | yes   |
| Microphone In       | x1  |



| Power supply unit | internal                   |
|-------------------|----------------------------|
| Power usage       | 63W typical, 1.2W stand by |



| Product dimensions W x H x D | 133.5 x 30 x 202mm |
|------------------------------|--------------------|
| Box dimensions W x H x D     | 192 x 72 x 267mm   |
| Weight (without box)         | .7kg               |
| Weight (with box)            | .9kg               |
| EAN code                     | 4948570032822      |

## 04

## **ENVIRONMENTAL CONDITIONS**

| Operation temperature range | 0°C - 45°C    |
|-----------------------------|---------------|
| Operation humidity          | 10% - 90%     |
| Storage temperature range   | - 20°C - 60°C |
| Storage humidity            | 10% - 90%     |

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED