


43" 4K gejming monitor koji garantuje vrhunski kvalitet slike

Upakovano u vrhunsku VA matricu i sa 8,3 miliona piksela (3840 x 2160) G-Master G4380UHSU čini idealnim ekranom za PC gejmere koji žele da se prebace na 4K rezoluciju. Uz MPRT vreme odziva od 0,4 ms i podršku za 144 Hz preko DisplayPort-a, ovaj monitor vam omogućava da donosite odluke u deliću sekunde i da zaboravite na efekte gosinga ili problema sa razmazivanjem slike.

Funkcija Black Tuner pruža bolje performanse gledanja u zasenčenim područjima ekrana, a sa ugrađenom opcijom FreeSync Premium, možete biti sigurni da će vaše omiljene igre od sada izgledati neverovatno oštre i realistične.



4K

UHD rezolucija (3840x2160), poznatija kao 4K, nudi gigantsko vidljivo područje sa 4 puta više informacija i radnim prostorom od Full HD ekrana. Zbog visokog DPI-ja (tačke po inču), prikazuje neverovatno oštre i jasne slike.



FreeSync™ Premium Tehnologija

Ovaj monitor garantuje nisku ulaznu latenciju i nizak framerate, čime se preventiraju bilo kakvi prekidi na bilo kojem framerate-u.

01 KARAKTERISTIKE EKRANA

Dijagonala	42.5", 108cm
Panel	VA matrica, haze 2%
Osnovna rezolucija	3840 x 2160 @144Hz (8.3 megapixel 4K UHD, DisplayPort)
Osnovna rezolucija	144Hz
Format ekrana	16:9
Osvetljenje	550 cd/m ²
Statički kontrast	4000:1
Napredni kontrast	80M:1
Vreme odziva (MPRT)	0.4ms
Zona gledanja	horizontalno/vertikalno: 178°/178°, desno/levo: 89°/89°, gore/dole: 89°/89°
Podržane boje	1.07B 10bit (8bit + Hi-FRC)
Horizontalna sinhronizacija	30 - 135KHz
Vidljiva površina Š x V	941.18 x 529.42mm, 37.1 x 20.8"
Razmak piksela	0.245mm
Boja	mat, crna

02 KONEKTORI / KONTROLE

Ulaz signala	HDMI x2 (v.2.0, max. 3840 x 2160 @60Hz - PS5/Xbox X S) DisplayPort x2 (v.1.4, max. 3840 x 2160 @144Hz)
USB HUB	x4 (v.3.2 (Gen 1, 5Gbit; DC5V, 900mA) x1, v.3.2 (Gen 1, 5Gbit; DC5V, 1.5A) x1, v.2.0 (DC5V, 500mA) x2)
HDCP	da
Priključak za slušalice	da

03 KARAKTERISTIKE

Smanjeno emitovanje plave svetlosti	da
Bez treperenja	da
Adaptive Sync podrška	DP: 3840 x 2160 @48-120Hz
Dodatno	kuka za slušalice
HDR	400
OSD jezici	EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL
Zvučnici	2 x 7W
Pogodnost	Kensington-lock™ priprema, DDC/CI, DDC2B, Mac OSX

04 MEHANIČKI

Podešavanje položaja prikaza	nagib
Ugao nagiba	10° gore; 2° dole
VESA montiranje	200 x 100mm

05 UKLJUČENI DODACI

Kablovi	Strujni kabl, USB, HDMI, DP
Ostalo	kratko uputstvo, bezbednosni vodič
Daljinski upravljač	da (baterije uključene)

06 UPRAVLJANJE NAPAJANJEM


Napajanje	interna
Potrošnja energije	% 1W tipično

07 ODRŽIVOST

Propisi	CE, TÜV-Bauart, EAC, PSE, RoHS podrška, ErP, WEEE, VCCI, REACH, UKCA
Klasa energetske efikasnosti (Regulation (EU) 2017/1369)	F
REACH SVHC	iznad 0.1%: Olova

08 DIMENZIJE / TEŽINA

Dimenzije proizvoda Š x V x D	977.5 x 621.5 x 251mm
Težina (bez kutije)	14.9kg
Težina (bez postolja)	13.1kg
EAN kod	4948570118526



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects.

© IYAMA CORPORATION. ALL RIGHTS RESERVED