

**UNIFIED COMMUNICATIONS****INFORMATION****Bluetooth Speakerphone for  
large meeting rooms**

The omnidirectional audio pickup from up to 5 meters with intelligent noise reduction and echo cancellation algorithms make the UC SPK01L the perfect choice for large meeting rooms. Guaranteeing seamless connection via Bluetooth, a USB cable or an audio cable this sleek looking speaker can be paired with up to 3 devices at the same.



## **Omnidirectional**

The UC SPK01L supports 360-degree omnidirectional audio pickup ensuring every voice in your meeting room is transmitted to the participants joining remotely.



## **High-quality voice experience**

This performance speaker with intelligent noise reduction and echo cancellation algorithms guarantees crystal clear sound for your calls.



## **Easy set up**

Seamless connection via Bluetooth, a USB cable or an audio cable. The speaker is instantly operational after connection.



## **Multiple device connectivity**

Connect up to 3 devices at the same time via Bluetooth, a USB cable and an audio cable.

## SPECIFICATION

### 01 SPEAKER

Maximum sound pressure level	85dB
Distortion	≤4%
Signal to noise ratio	80dB
Frequency range	150Hz ~ 16kHz

### 02 MICROPHONE

Number of microphone arrays	x6
Voice pickup range	5m (radius)
Frequency range	150Hz ~ 8kHz

### 03 CONNECTIVITY & BUTTON OPERATIONS

USB Type C	x1 (Audio In/Out, Charge 5V/2A)
AUX	x1 (In/Out, 3.5mm, DaisyChain)
Bluetooth	4.2+EDR
Buttons	Power, Volume, Bluetooth, Mute, Answer/Hang up

### 04 ACCESSORIES & BATTERY

Bluetooth receiver	yes
USB (type A to C) cable	yes
Audio cable	yes
Battery capacity	7.4V/2200mAh
Charging	wired 5V/2A, wireless 5W
Battery life on a single charge	8 hours

### 05 SUSTAINABILITY

Regulations	CE, RoHS support, ErP, WEEE, REACH
-------------	------------------------------------

### 06 DIMENSIONS / WEIGHT

Weight (without box)	0.4kg
EAN code	4948570033041



All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-9241-307:2008 in connection with pixel defects. © Iiyama Corporation. ALL RIGHTS RESERVED