



21.5" Full HD monitor featuring a VA Panel and FreeSync

The ProLite X2283HSU-B1 is a 21.5" screen featuring a VA panel which guarantees accurate and consistent colour reproduction with wide viewing angles. The monitor is equipped with speakers, headphone socket, HDMI and DisplayPort connections, a 2-port USB-Hub, a blue light reducer function to reduce eye fatigue and compatible with iiyama desktop arms for multiscreen productivity solutions. Featuring a 1ms response time, and FreeSync, this desktop monitor is suitable for the home office environment and casual gaming.

TCO conformity and ultra-low power consumption meet the best standards for environmentally conscious business users, universities and government agencies.



Flicker-free + Blue light

The ultimate solution for the comfort and health of your eyes. Flicker-free monitors with the blue light reducer function substantially reduce the strain and fatigue caused by flickering and blue light emittance of regular monitors.



OverDrive ON / OFF

When very fast graphics are displayed your monitor can sometimes get blurry. Turning on the OverDrive feature will eliminate that.

01 DISPLAY CHARACTERISTICS

Diagonal	21.5", 54.5cm
Panel	VA LED, matte finish
Native resolution	1920 x 1080 @75Hz (DisplayPort&HDMI, 2.1 megapixel Full HD)
Aspect ratio	16:9
Panel brightness	250 cd/m ²
Static contrast	3 000:1
Advanced contrast	80M:1
Response time (MPRT)	1ms
Viewing zone	horizontal/vertical: 178°/178°, right/left: 89°/89°, up/down: 89°/89°
Colour support	16.7mIn (sRGB: 99%; NTSC: 72%)
Horizontal Sync	30 - 85kHz
Viewable area W x H	478.7 x 260.3mm, 18.8 x 10.2"
Pixel pitch	0.249mm
Colour	matte, black

02 INTERFACES / CONNECTORS / CONTROLS

Signal input	HDMI x1 DisplayPort x1
USB HUB	x2 (v.2.0 (DC5V, 500mA))
HDCP	yes
Headphone connector	yes

03 FEATURES

Blue light reducer	yes
Flicker free	yes
Adaptive Sync support	yes
OSD languages	EN, DE, FR, ES, IT, RU, JP, CZ, NL, PL
Control buttons	Navigation buttons: Push, Up (up/ i-Style colour/Blue Light Reducer), Down (down/ input select), Left (left/ Eco), Right (right/ volume)
User controls	picture adjust (brightness, contrast, ECO, Blue Light Reducer, ACR, OD, MBR), colour settings (colour temperature, user preset, i-Style colour), OSD (OSD H. position OSD V. position, OSD time), language, recall, miscellaneous (sharp and soft, video mode adjust, opening logo, AMD FreeSync, RGB range, display information), input select (source), audio settings (volume, mute)
Speakers	2 x 2W
Convenience	Kensington-lock™ prepared, DDC2B, Mac OSX

04 MECHANICAL

Display position adjustments	tilt
Tilt angle	22° up; 4° down
VESA mounting	100 x 100mm
Cable management system	yes

05 ACCESSORIES INCLUDED

Cables	power, USB, HDMI
--------	------------------

Other

quick start guide, safety guide

06 POWER MANAGEMENT

Power supply unit

internal

Power supply

AC 100 - 240V, 50/60Hz

Power usage

17W typical, 0.5W stand by, 0.3W off mode

07 SUSTAINABILITY

Regulations

TCO Certified, CE, TÜV-Bauart, EAC, VCCI-B, PSE, RoHS support, ErP, WEEE, REACH, UKCA

TCO Certified

X2283HSU-B1 H

Energy efficiency class (Regulation (EU) 2017/1369)

E

REACH SVHC

above 0.1%: Lead

08 DIMENSIONS / WEIGHT

Product dimensions W x H x D

500 x 365 x 183.5mm

Box dimensions W x H x D

565 x 128 x 394mm

Weight (without box)

3.1kg

Weight (with box)

4.5kg

EAN code

4948570120697



